



CALISTER

Bauhaus Manual

| | |
|----------|-------------|
| Cal. 585 | Cal. 6003.D |
| Cal. 505 | Cal. 6004.D |
| Cal. 515 | Cal. 6003.B |
| | Cal. 6004.B |



Pos. I Position of rest (watch running)

Pos. II Quick-change correction for date

The date can also be corrected during the day-changing phase between 10 pm and midnight. The date of the following day has to be set, because no automatic date change takes place at midnight.

- Pull the crown out to position II (watch still running).
- Turn the crown clockwise until the required date appears.

Cal. 6003.D & 6004.D:

- Turn the crown until the required date appears.
- Push the crown back into position I.

Pos. III Setting the time

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.

| | |
|----------|------------|
| Cal. 774 | Cal. 715Li |
| Cal. 775 | |
| Cal. 704 | Cal. 1005 |
| Cal. 705 | Cal. 1006 |
| Cal. 784 | Cal. 1009 |
| Cal. 785 | Cal. 1015 |
| Cal. 714 | Cal. 1016 |
| Cal. 715 | Cal. 1019 |



Pos. I Position of rest (watch running)

Pos. II Quick-change correction for date

Blocking time for the quick-change day correction is from approx. 9.30 pm and midnight.

- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears.
- Push the crown back into position I.

Pos. III Setting the time

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.

| |
|-------------|
| Cal. 7002.B |
| Cal. 7003.B |
| Cal. 7004.B |



Pos. I Position of rest (watch running)

Pos. II Quick-change correction for date

The date can also be changed during the day-changing phase between approx. 8.00 pm and midnight.

The date of the following day has to be set, because no automatic date change takes place at midnight.

- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears.
- Push the crown back into position I.

Pos. III Setting the time

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.